



| MODEL | A | B | C | MODEL | A | B | C |
|----------------|-------|------|------|------------------|-----|-----|------|
| MCL-24 LOCK | 4.625 | 1.14 | 0.75 | MCL-24 STRIKE | 3.1 | 1.1 | 0.25 |

MAGNETIC CABINET LOCK - MODEL MCL-24:

Features

- Fail safe
- Fits in most size limited applications
- Unlimited operating life
- Suitable for outdoor use
- 200 lbs. holding force
- Low current draw (62 mA @ 24VDC)
- All ferrous metal surfaces plated to MIL specification
- Operating environment -40F to 140F [-40C to 60C]
- 10 ft cable included
- Self aligns to operate reliably
- Fail Safe

Operating Temperature

-40 to 60 C [-40 to 140 F]



MAGNETIC CABINET LOCK - MODEL MCL-24 (cont'd)

How to Order

| <u>Part #</u> | <u>Description</u> |
|---------------|-----------------------------|
| MCL-24 | Magnetic Cabinet Lock 24VDC |

Architectural Specifications

- A. The MCL-24 Magnetic Cabinet Lock shall be produced by an ISO 9001 certified manufacturer
- B. The Magnetic Cabinet Lock shall have a limited lifetime warranty covering malfunction and abuse.
- C. The LOCK shall only be available in a 24VDC model.
- D. The LOCK shall be fail safe and fit into most size limited applications.
- E. The LOCK shall have 200 pounds of holding force and shall provide a strong level of security for cabinet locking applications.
- F. The LOCK shall support outdoor use or use where the cabinet will be released for extended periods of time.